

## SPECIFICATIONS

Plank size	Length: 630-1860 mm Width: 190 mm Thickness: 14(3.5) mm
Box	Min 5 planks of 1.86 m 2.12 m <sup>2</sup> 16.5 kg
Pallet	50 boxes
Structure	3-layer
Coating	UV mat lacquer
Texture	Slightly brushed
Standard colour	Pure Plus, Wheat, Coffee, Skyline Grey, Natural, Sunset
Grading	Rustic A+
Top layer type	Dry sawn veneer
Top layer thickness	3.5 mm
Bevel	V-groove on the 4 sides
Gloss	10 ± 5%
Locking system	Drop Lock click system
Type of installation	Advised: floating

## STRUCTURE



## INSTALLATION



## PRODUCT CHARACTERISTICS - General

Factor	Standard - EN 14342
Density	650 kg/m <sup>3</sup> , 14 mm
Reaction to fire	Dfl-S1
Formaldehyde emission	E1
PCP	≤ 5 ppm
Thermal conductivity	0.10 W/mK
Thermal resistance	0.14 m <sup>2</sup> K/W
Biological durability	Class 1
Surface soundness	-
Impact resistance	ECO
Moisture level	7% - ±2%
Floor heating	Allowed, according to specific standards